



Revision Number: 001.3

Issue date: 05/23/2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LePage Epoxy Hardener	IDH number:	1442482
Product type/use:	2-Component epoxy adhesive	Item number:	1443835_1372554
Restriction of Use:	None identified	Region:	Canada
Company address:	Contact information:		
Henkel Canada Corporation	Telephone: +1 (905) 814-6511		
Meadowpine Boulevard 2515	MEDICAL EMERGENCY Phone: Poison Control Center		
Mississauga, Ontario L5N 6C3	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: ABRASION COULD RELEASE RESPIRABLE PARTICLES OF SILICA QUARTZ, A CANCER HAZARD BY INHALATION. NORMAL USE OF THIS PRODUCT CAUSES NO SUCH RELEASE.

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1C - Corrosive
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

IDH number: 1442482

Product name: LePage Epoxy Hardener

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Quartz (SiO ₂), <1% respirable	14808-60-7	30 - 60
Limestone	1317-65-3	5 - 10
Benzyl alcohol	100-51-6	5 - 10
Calcium carbonate	471-34-1	5 - 10
3- Aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	5 - 10
1,3-Propanediamine, N-[3-(tridecyloxy)propyl]-, branched	68479-04-9	5 - 10
Titanium dioxide	13463-67-7	1 - 5
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	1 - 5
N-Aminoethylpiperazine	140-31-8	1 - 5
4-Tert-butylphenol	98-54-4	1 - 5
Bis[(dimethylamino)methyl]phenol	71074-89-0	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Get immediate medical attention.
Symptoms:	See Section 11.
Notes to physician:	Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Use dry chemical, water spray or carbon dioxide. Alcohol-resistant foam.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Caution should be exercised when using water or foam as frothing may occur. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Decomposition and combustion products may be toxic.

Hazardous combustion products:

Oxides of carbon. Oxides of nitrogen. Ammonia.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not allow product to enter sewer or waterways. Wear appropriate protective equipment and clothing during clean-up. Prevent further leakage or spillage if safe to do so.

Clean-up methods:

Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:

Avoid breathing dust. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Avoid contact with eyes, skin and clothing.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Canada Customer Service at 800-263-5043.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Quartz (SiO ₂), <1% respirable	0.025 mg/m ³ TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable. 0.05 mg/m ³ TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m ³ OSHA_ACT (Respirable dust.) 0.05 mg/m ³ PEL Respirable dust.	None	None
Limestone	10 mg/m ³ TWA Total dust.	5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust.	None	None
Benzyl alcohol	None	None	10 ppm (44.20 mg/m ³) TWA	None
Calcium carbonate	None	5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust.	None	None
3- Aminomethyl-3,5,5-trimethylcyclohexylamine	None	None	None	None
1,3-Propanediamine, N-[3-(tridecyloxy)propyl]-, branched	None	None	None	None
Titanium dioxide	10 mg/m ³ TWA	15 mg/m ³ PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m ³ TWA Respirable fraction.	None	None
2,4,6-Tris(dimethylaminomethyl)phenol	None	None	None	None
N-Aminoethylpiperazine	None	None	None	None
4-Tert-butylphenol	None	None	None	None
Bis[(dimethylamino)methyl]phenol	None	None	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Chemical resistant, impermeable gloves. Nitrile gloves. Neoprene gloves. Butyl rubber gloves. Viton gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Liquid

Color:

white

Odor:

Mercaptan

Odor threshold:

Not available.

pH:

Not available.

Vapor pressure:

Not available.

Boiling point/range:

Not available.

Melting point/ range:

Not available.

Specific gravity:

1.49

Vapor density:

Not available.

Flash point:	> 93 °C (> 199.4 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	10.60 %
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Not available.
Incompatible materials:	Strong Lewis acids. Strong bases. Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: Mists, vapors or liquid may cause severe irritation or burns. May be harmful if inhaled.
Skin contact: Causes skin burns. May cause allergic skin reaction.
Eye contact: Causes eye burns. Blurred vision. Excess tearing.
Ingestion: May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Quartz (SiO2), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity
Limestone	None	Nuisance dust
Benzyl alcohol	Oral LD50 (Rabbit) = 1,940 mg/kg Oral LD50 (Rat) = 1,230 - 3,100 mg/kg Oral LD50 (Mouse) = 1,580 mg/kg Oral LD50 (Rat) = 3,100 mg/kg Dermal LD50 (Rabbit) = 2,000 mg/kg	Allergen, Central nervous system, Corrosive, Irritant
Calcium carbonate	Oral LD50 (Rat) = 6,450 mg/kg Oral LD50 (Mouse) = 6,450 mg/kg	Nuisance dust
3- Aminomethyl-3,5,5-trimethylcyclohexylamine	None	Irritant, Allergen, Corrosive, Lung
1,3-Propanediamine, N-[3-(tridecyloxy)propyl]-, branched	None	No Target Organs
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
2,4,6-Tris(dimethylaminomethyl)phenol	None	Irritant, Allergen
N-Aminoethylpiperazine	None	Irritant, Corrosive, Allergen
4-Tert-butylphenol	None	Irritant, Allergen, Skin, Corrosive
Bis(dimethylamino)methylphenol	None	No Records

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Quartz (SiO2), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes
Limestone	No	No	No
Benzyl alcohol	No	No	No
Calcium carbonate	No	No	No
3- Aminomethyl-3,5,5-trimethylcyclohexylamine	No	No	No
1,3-Propanediamine, N-[3-(tridecyloxy)propyl]-, branched	No	No	No
Titanium dioxide	No	Group 2B	No
2,4,6-Tris(dimethylaminomethyl)phenol	No	No	No
N-Aminoethylpiperazine	No	No	No
4-Tert-butylphenol	No	No	No
Bis(dimethylamino)methylphenol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine, 1,3-Propanediamine, N-[3-(tridecyloxy)propyl]-, branched)
Hazard class or division: 8
Identification number: UN 2735
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Isophoronediamine, 1,3-Propanediamine, N-[3-(tridecyloxy)propyl]-, branched)
Hazard class or division: 8
Identification number: UN 2735
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine, 1,3-Propanediamine, N-[3-(tridecyloxy)propyl]-, branched)
Hazard class or division: 8
Identification number: UN 2735
Packing group: III
Marine pollutant: 1,3-Propanediamine, N-[3-(tridecyloxy)propyl]-, branched

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 3

Prepared by: Product Safety and Regulatory Affairs

Issue date: 05/23/2019

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.