



Revision Number: 003.1

Issue date: 03/21/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite Extreme Gel Glue **IDH number:** 2596210
Product type/use: Contact adhesive **Region:** United States
Restriction of Use: None identified **Contact information:**
Company address: Henkel Corporation Telephone: +1 (860) 571-5100
 One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center
 Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkeln.com

This product contains one or more components regulated under a Significant New Use Rule (SNUR) by the US EPA. See Section 15 for more information.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
WARNING:	COMBUSTIBLE LIQUID. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)

Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Wash contaminated clothing before reuse. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Silica, amorphous, fumed, cryst.-free	112945-52-5	5 - 10
Trimethoxyvinylsilane	2768-02-7	0.1 - 1

IDH number: 2596210

Product name: Loctite Extreme Gel Glue

Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	0.1 - 1
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	0.1 - 1
Methanol	67-56-1	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact:	Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek medical attention.
Ingestion:	If material is ingested, immediately contact a physician or poison control center. Do not induce vomiting.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear protective equipment. Wear self contained breathing apparatus.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Acrid smoke and fumes. Oxides of carbon. Silicon dioxide Calcium oxide.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling:	Do not handle or store near an open flame, heat or other sources of ignition. Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation. Use only in well-ventilated areas. Wear suitable protective clothing, safety glasses and gloves. Keep out of the reach of children.
Storage:	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. Provide adequate ventilation.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silica, amorphous, fumed, cryst.-free	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Trimethoxyvinylsilane	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	None	None	None	None
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	None	None	None	None
Methanol	200 ppm TWA 250 ppm STEL (SKIN)	200 ppm (260 mg/m3) PEL	None	None

Engineering controls:	Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.
Respiratory protection:	In case of insufficient ventilation wear suitable respiratory equipment. Respirator with combination filter for vapor/particulate.
Eye/face protection:	Wear safety glasses with side shields. Do not wear contact lenses.
Skin protection:	Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	high viscosity, liquid
Color:	Colorless, clear
Odor:	Odorless
Odor threshold:	Not available.
pH:	Not applicable
pH:	Not applicable
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	1.1740
Vapor density:	Not available.
Flash point:	68 - 72 °C (154.4 - 161.6 °F)
Flammable/Explosive limits - lower:	1.4 %
Flammable/Explosive limits - upper:	50 %
Autoignition temperature:	Not applicable
Flammability:	Not applicable
Evaporation rate:	Not determined
Solubility in water:	Partially soluble
Partition coefficient (n-octanol/water):	Not determined
VOC content:	14.46 %; 131.6 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
Viscosity:	150,000 - 200,000 mPa.s
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Methanol is liberated slowly upon exposure to moisture.
Incompatible materials:	None if used for intended purpose.
Reactivity:	Not available.
Conditions to avoid:	Direct sources of heat. Do not freeze. Humidity

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Eyes, Inhalation

Potential Health Effects/Symptoms

Inhalation:	May be harmful if inhaled. Methanol is released during application and cure, which may affect the nervous system causing dizziness, headache or nausea.
Skin contact:	Repeated or prolonged skin contact may result in allergic sensitization. Persons with previous allergic reactions to amines should avoid contact with product.
Eye contact:	Contact with uncured product may irritate the eyes. Vapors may also produce eye irritation.
Ingestion:	May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Silica, amorphous, fumed, cryst.-free	None	No Data
Trimethoxyvinylsilane	Inhalation LC50 (Rat, 4 h) = 2773 ppm	Irritant, Allergen
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Inhalation LC50 (Rat, 4 h) = > 1.49 - < 2.44 mg/l	Irritant, Allergen
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Inhalation LC50 (Rat, 4 h) = 500 mg/m3	No Data
Methanol	Oral LD50 (Rat) = 5,628 mg/kg Oral LD50 (Mouse) = 7,300 mg/kg Oral LD50 (Rabbit) = 14.4 g/kg Dermal LD50 (Rabbit) = 15,800 mg/kg	Eyes, Irritant, Metabolic, Nervous System

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silica, amorphous, fumed, cryst.-free	No	No	No
Trimethoxyvinylsilane	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	No	No	No
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	No	No	No
Methanol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Combustible liquid, n.o.s. (Vinyltrimethoxysilane)
Hazard class or division: Combustible Liquid
Identification number: NA 1993
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 5(a) SNUR: This product contains the following component(s) subject to a Significant New Use Rule (SNUR) by the US EPA: Mercury (CAS # 7439-97-6). The SNUR is codified at Section number: 40 CFR 721.10068

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.
Ethylene diamine (CAS# 107-15-3).

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 8, 11, 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 03/21/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.